



Internal hex




DIN ISO1173

ITEM NO.	Ø	l mm	1/4" drive
27080	1.5	25	C6.3
27081	2	25	C6.3
27082	2.5	25	C6.3
27083	3	25	C6.3
27084	4	25	C6.3
27085	5	25	C6.3
27086	6	25	C6.3
27087	8	25	C6.3




DIN ISO1173

ITEM NO.	Ø	l mm	5/16" drive
27851	4	30	C8
27852	5	30	C8
27853	6	30	C8
27854	7	30	C8
27855	8	30	C8
27856	10	30	C8



DIN ISO1173


ITEM NO.	Ø	l mm	1/4" drive
27193	3	50	E6.3
27194	4	50	E6.3
27195	5	50	E6.3
27196	6	50	E6.3
27198	8	50	E6.3



DIN ISO1173

ITEM NO.	Ø	l mm	5.5 mm drive
30753	3	50	A5.5
30754	4	50	A5.5
30755	5	50	A5.5
30756	6	50	A5.5
30758	8	50	A5.5


Ball-end



DIN ISO1173

ITEM NO.	Ø	l mm	1/4" drive
27183	3	50	E6.3
27184	4	50	E6.3
27185	5	50	E6.3
27186	6	50	E6.3


External hex



Magnetic
DIN ISO1173

ITEM NO.	Ø	l mm	1/4" drive
26231	5	45	E6.3
26232	5.5	45	E6.3
26233	6	45	E6.3
26234	7	45	E6.3
26235	8	45	E6.3
26236	9	45	E6.3
26237	10	45	E6.3
26238	11	45	E6.3
26239	12	45	E6.3
26240	13	45	E6.3
26241	1/4"	45	E6.3
26242	3/8"	45	E6.3
26243	5/16"	45	E6.3


TRI-WING



DIN ISO1173

ITEM NO.	Ø	l mm	1/4" drive
27480	TW 0	25	C6.3
27481	TW 1	25	C6.3
27482	TW 2	25	C6.3
27483	TW 3	25	C6.3
27484	TW 4	25	C6.3
27485	TW 5	25	C6.3


1/4" Adapters




DIN ISO1173

ITEM NO.	Ø	l mm	1/4" drive
26298	1/4"	25	C6.3
26398	1/4"	50	C6.3


Double-ended bits




ITEM NO.	+	+	l mm	1/4" drive
29010	PH 1	PZ 1	60	6.3 mm
29011	PH 2	PZ 2	60	6.3 mm
29012	PH 3	PZ 3	60	6.3 mm




ITEM NO.	+	-	l mm	1/4" drive
29001	PH 1	0.6 x 4.5	60	6.3 mm
29002	PH 2	0.8 x 5.5	60	6.3 mm
29003	PH 3	1.0 x 6.0	60	6.3 mm



ITEM NO.	+	-	l mm	1/4" drive
29004	PZ 1	0.6 x 4.5	60	6.3 mm
29005	PZ 2	0.8 x 5.5	60	6.3 mm
29006	PZ 3	1.0 x 6.0	60	6.3 mm



ITEM NO.	-	-	l mm	1/4" drive
29007	0.5 x 3.0	0.6 x 4.5	60	6.3 mm
29008	0.8 x 5.5	1.0 x 6.0	60	6.3 mm
29009	1.2 x 6.5	1.6 x 8.0	60	6.3 mm



ITEM NO.	+	+	l mm	1/4" drive
29016	T 10	T 15	60	6.3 mm
29017	T 20	T 25	60	6.3 mm
29018	T 30	T 40	60	6.3 mm